

# LED STANDARD WALL PACK



## FEATURES & BENEFITS

- Modular design allows for easy installation, replacement and maintenance. This design also creates a chimney effect which provides exceptional thermal management.
- Corrosion resistant polyester powder painted 100µ m thickness.
- Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
- Over 20 optical lenses are available for virtually any application.
- High quality LEDs, driver and components, e.g. MOLEX, WAGO connectors.
- Multiple lighting control options are available, e.g. DALI, 1-10V
- 5 years limited warranty.
- Nichia 3535 LED Chips / Philips Advance Xitanium LED Driver.


\*IDA Approved if color temperature is 3000K or less\*

## CERTIFICATIONS

UL/ CUL/ LM79/ SAA/ ENEC/ CB/ CE/ ErP/ RoHS/ IK08

## TECHNICAL PARAMETERS

<b>Power</b>	20-160W
<b>Input</b>	120-277VAC or 220-240VAC or 347-480VAC
<b>PF</b>	>0.95
<b>THD</b>	<20%
<b>L85</b>	>60,000H
<b>Operating Temperature</b>	-40°C ~ +50°C
<b>Efficacy</b>	125 - 135 lm/W
<b>ANSI CCT</b>	3000K/4000K/5000K/5700K
<b>Min CRI</b>	70 or 80 or 85
<b>IP Rating</b>	IP65
<b>SPD</b>	Optional
<b>DALI</b>	Optional
<b>1-10V</b>	Optional
<b>Photocell</b>	/
<b>Smart Control</b>	/
<b>Optic (IESNA)</b>	Type I, Type II, Type III, Type IV, Type V
<b>Color Options</b>	Grey/Black/Bronze/White



## ORDERING INFORMATION

Example : SESWP-80-A1-50K-T4M-BK

Fixture	Power (Watts) (40W/module)	Voltage	Color Temperature (CCT)	Light Distribution (Lens Type)	Fixture Color	Mounting Options (Brackets)	Lighting Controls	Accessory Info
SESWP - Standard Wall Pack	20 - 2,600 lumens	A1: 120-277V AC	30K - 3000K	T1M1 - Type I Medium	GR - Grey BK - Black BZ - Bronze WH - White CU - Custom*	W - Wall Mount	00	BLS - Back Light Shield**
	30 - 3,900 lumens		40K - 4000K	T2M1 - Type II Medium			Not required	RO - Rotated Optics**
	40 - 5,200 lumens	B4: 347-480V AC	50K - 5000K	T3M1 - Type III Medium			01	Bird Spike
	60 - 7,800 lumens		57K - 5700K	T3L1 - Type III Long			Photocell	20KA Surge
	80 - 10,400 lumens	AM - Turtle	50K - 5000K	T4S1 - Type IV Short			02	Protection Device
	90 - 11,700 lumens	Safe Amber	57K - 5700K	T4M1 - Type IV Medium			Motion Sensor	Safety Cable
	120 - 15,600 lumens		57K - 5700K	T5U - 10°			03	EM - Emergency
	160 - 20,800 lumens		57K - 5700K	T5V - 25°			Photocell + Motion Sensor	Backup
			57K - 5700K	T5W - 40°			04	
			57K - 5700K	T5S - 60°			DALI	
			57K - 5700K	T5M - 90°			05	
			57K - 5700K	T5L - 120°			1-10V dimming	
			57K - 5700K	TSX - 150°				
		57K - 5700K	T5D - Type V Diffuser					

\*Extra cost for custom color

\*\*Note this after lens type.